



MAG2000 Impact Date/Timer

SET UP INSTRUCTIONS

The MAG 2000 Impact Date/Timer is a MAG 2000 that provides the date and time of an impact.

The MAG 2000 Impact Date/Timer uses the same proven technology as the MAG 2000, so to set or reset the indicator magnet inside the unit, follow these instructions.


To set and enable the Impact Date/Timer, please follow this procedure:

1. To unlock the cover, use the ring shaped key. Place the ring key around the cover inserting the 4 prongs through the 4 slots in the cover.
2. Press firmly down on the ring key and while holding the downward pressure, turn the key slightly to the left (counter-clockwise) until the cover loosens. Excessive torque is not needed.
3. Remove the key and then grasp the cover and turn it left (counter-clockwise) as far as possible.
4. Lift the cover off and put the **red indicator magnet** back to the center position (red side up).

NOTE: Be careful to keep finger prints and debris off of the insides of the unit, and off of the bottom of the indicator magnet.



5. On the back of the clock, you will see two silver buttons at the bottom of the unit. The button on the left is labeled "SET" (written above button) and the button on the right is labeled "MODE" (written above button). These two buttons will be used to set the clock time.
6. Turn the clock over to view the date and time.
7. Press and release the MODE button one time. The "Shock Time" message will disappear.
8. Press and hold the MODE button until the "month" digit begins flashing. Release the MODE button.
9. Use the SET button to adjust the month digit to the desired value.
10. Press and release the MODE button one time. The "day" digit will begin flashing.
11. Use the SET button to adjust the day digit to the desired value.
12. Repeat this process until all time and date changes have been made.
13. Once completed, Place the cover back on. Press down and turn right (Clockwise) as far as possible. This will latch the cover back in place.
14. Then affix the unit, using the adhesive or screws in the holes provided, and companion label to the desired location.



Your shipment is now monitored. Once an impact occurs above the rated value of the MAG 2000 Impact Date / Timer, the clock display will freeze at the time and date of impact and the Shock Time indicator will blink. This information should be noted by the receiver on the bill of lading and the contents of the package should be inspected for damage.

Re-setting the MAG 2000 Date / Timer is as simple as removing the cover, repositioning the indicator magnet to it's center position and replacing the cover. **NOTE:** The clock will automatically display the current time and date after it is placed back on the base unit. (Requires 1 minute of inactivity.)