

## Gain Value-added Insights into Your Supply Chain

Monitoring temperature sensitive products throughout the supply chain is imperative to identify exposure to conditions that could cause product quality issues, decreases in efficacy, or a health and safety concerns for consumers.

CustomSense™ electronic indicators provide an accurate and clearly visible indication when a shipment has experienced a temperature excursion outside of the product guidelines. A monitoring program using CustomSense will identify potential quality issues before they reach customers and provide traceability and accountability for issues across the supply chain.

## CustomSense™ Product Features & Benefits

### Easy to Use

- **Simple Activation** with the push of a button on the front of the indicator
- **Large Print** display of temperature ranges to avoid confusion of what is being monitored
- **Clear LED Indication of Pass/Fail** takes guesswork out of determining product status
- **Adhesive Backing** making it easy to affix indicator to package or product surface
- **Four Pre-programmed Temperature Ranges** that cover life sciences monitoring needs



CSTI	CRT	Freeze	Frozen
Certain vaccines, Injection medications, Compounded Medications, Test Samples	Creams, Test Kits, Test Samples	Certain vaccines, Chemicals, Paints	Certain vaccines, Tissue samples - human/animal, Frozen foods

## Precision, Accuracy, & Quality

- **Monitors Temperature** at 5-minute intervals
- **Indicates** cumulative excursion of 30 minutes or more
- **Temperature Accuracy** of +/- 0.5C from 0°C - 80°C
- **Battery Life** of 3 years on the shelf and 90 days once activated
- **NIST® Traceable** by device



## Tamper Avoidance

- **Activation** is irreversible so indicators cannot be stopped during a journey
- **Indicators are Serialized** with unique identifier and matching label to apply to shipping documents for verification

Specifications	
<b>Monitoring Options</b>	Single-use: Refrigerated, Freeze, CRT, Frozen, Custom
<b>Operating Temperature Range</b>	-40°C to 80°C
<b>Temperature Accuracy</b>	±0.5°C from 0°C to 80°C ±1°C from -25°C to 0°C ±2°C from -40°C to -25°C
<b>Data Storage Capacity</b>	None
<b>Battery Life</b>	3 year shelf life (room temperature) 90 days once activated
<b>Battery Type</b>	Lithium Coin Cell
<b>Device Enclosure</b>	Stratatac All-Temperature Permanent Adhesive PETG IP67, NEMA 6 Rated
<b>Dimensions</b>	4.45" (113mm) x 2.80" (71mm) x .280" (7mm) Weight: .60 oz (17g)
<b>Quality Certificates</b>	NIST® traceable by device Intertek Certified CE
<b>Indicator LEDs</b>	The indicator LEDs will flash based on the status of the indicator: - Indicator ON, Acclimating: "Within Range" flashes twice every 4 seconds - Indicator ON, Within Range: "Within Range" flashes once every 4 seconds - Indicator ON, High Excursion: "Exceed High Limit" flashes once every 4 seconds - Indicator ON, Low Excursion: "Exceed Low Limit" flashes once every 4 seconds

Standard Products <sup>1</sup>	CSTI-0208	CSTI-FREZ	CSTI-CRT	CSTI-FRZN
<b>Temperature Excursion Settings</b>	<b>High</b> 8°C <b>Low</b> 2°C	<b>High</b> N/A <b>Low</b> 0°C	<b>High</b> 25°C <b>Low</b> 15°C	<b>High</b> -15°C <b>Low</b> -25°C
<b>Measurement Interval</b>	5 minutes			
<b>Start-up/Acclimation Delay Time</b>	30 minutes			
<b>Alarm Setting</b>	30 minutes cumulative time over or under excursion points required to trigger excursion indication			

<sup>1</sup> Products can be configured to specific requirements based on a minimum order quantity of 10,000 units. Contact us for more information.