



SHOCK WATCH[®]

Damage Prevention and Safety Solution

ShockWatch Label Impact Indicator Mounting Instructions

- Rule 1: Place labels on th eright edge of the shipment
- **Rule 2:** Avoid the centre of the package; the mounting location should be structurally sound
- Rule 3: Place labels on the longest side of the package
- Rule 4: The heavier the shipment, the lower the label should be mounted
- **Rule 5:** Place the Alert Sticker on the bill of lading as a reminder for receivers to check the indicator immediately upon arrival

Recommended Placement



L-30 100G (Green) and L-35 75G (Orange)

Place label on upper right corner of the package.





L-47 50G (Red)

Packages 22.68-45.36kg (50-100lbs): Place label on upper right corner of the package (Position A).

Packages 45.36-226.8kg (100-500lbs): Place label along right edge, at least 61cm (24 inches) from the bottom of the package (Position B).













Recommended Placement





L-55 37G (Purple)

Packages 22.68-45.36kg (50-100lbs): Place label on upper right corner of the package (Position A).

Packages 45.36-226.8kg (100-500lbs): Place label along right edge, at least 30.5-61cm (12-24 inches) from the bottom of the package (Position B).

If the package is twice as long as it is wide, use two ShockWatch Label Indicators. Place a second Indicator in the same position on the opposite side of the package.









Place label 30.5-35.5cm (12-24 inches) from the bottom of the box. Optional: Place a second indicator in the same position on the opposite side of the package.

If the package is twice as long as it is wide, use two ShockWatch Label Indicators. Place a second Indicator in the same position on the opposite side of the package.

While these instructions are considered best practices, each situation may be different. If you have any further questions or would like to reorder, please either email us at **solutions@shockwatch.com.au** or call **1300 074 625**.



