



ShockWatch Label Impact Indicators



- Acts as a visual deterrent to improper handling
- Provides indisputable evidence of mishandling
- Promotes chain of accountability for all product handling
- Confirms effectiveness of packaging
- Helps identify trouble spots in supply chain, from production to transportation and storage

Protect your investments. Drive down damages. Improve your margins.

ShockWatch Label Impact Indicators are a cost-effective solution that detects the mishandling of products and packages during shipment. Alerting handlers that a package is being monitored and requires extra care will ultimately reduce damage-related costs. ShockWatch Label Impact Indicators are

tamper-proof, mechanically-activated devices that turn red when a potentially damaging impact occurs.

ShockWatch Label Impact Indicators are a simple solution for identifying shipments that may be damaged and driving accountability in the supply chain, and are a proven visual deterrent to reduce damage by up to 60%.



Sensitivity range between
25 – 100G



ShockWatch Label Impact Indicator
with Companion Label



Selection Guide

Selecting the right ShockWatch Label Indicator is a simple process. Start with your shipment size and weight. The selection guide provides a starting point

for sensitivity selection. The Indicator best suited to your application will also take into account product fragility and packaging. More fragile products

may require a more sensitive (lower G-force) Indicator while products with more robust packaging may need a less sensitive (higher G-force) Indicator.

| | 0 - 0.03m ³ | 0.03 - 0.14m ³ | 0.14 - 0.42m ³ | 0.42 - 1.42m ³ | +1.42m ³ |
|-------------|------------------------|---------------------------|---------------------------|---------------------------|---------------------|
| 0 - 5kg | 100G | 100G | 75G | 75G | 50G |
| 5 - 11kg | 100G | 75G | 75G | 50G | 50G |
| 11 - 23kg | 75G | 75G | 50G | 50G | 37G |
| 23 - 45kg | 75G | 50G | 50G | 37G | 37G |
| 45 - 113kg | 50G | 50G | 37G | 37G | 25G |
| 113 - 454kg | 50G | 50G | 37G | 25G | 25G |
| +454kg | – | 37G | 25G | 25G | 25G |

Specifications

| | |
|-------------------------------------|---|
| Sensitivity Range | 25 – 100G |
| Impact Duration | 0.5 – 50ms |
| Tolerance | ±15% at 20°C / 68°F, 1 ATM |
| Operating Temperature | -25°C – 80°C / -13°F – 176°F |
| Security | Tamper-proof, serialised (optional) |
| Shelf Life / Storage Recommendation | 2 years stored at 20°C / 68°F, 1 ATM. 0-99% RH Non-condensing |
| Dimensions | 96.52mm x 96.52mm |
| Weight | ~2.37g (varies by sensitivity) |
| Adhesive | Acrylic |