



MAG 2000 Impact Recorder



- Acts as a visual deterrent to improper handling
- Reduces mishandling through awareness
- Provides indisputable evidence of mishandling
- Promotes chain of accountability for all product handling
- Confirms effectiveness of packaging
- Helps identify trouble spots in supply chain, from production to transportation and storage

Save Money. Save Time. Deter Mishandling. The MAG 2000 impact indicator is a cost-effective, resettable and reusable device designed to monitor the handling of fragile goods and freight containers greater than 500 lbs. It provides an indisputable record of how your shipment is handled.

The device is also widely used on rail cars and trucking fleets to monitor for excessive impacts during humping or latching.

While MAG 2000 can be used on either a product or the product packaging, it is generally advisable that the MAG 2000 be placed on the product since the

impact experienced by the product itself is generally more important than the impact received by the packaging. The placement of the MAG 2000 will affect the selection of the proper sensitivity.



Selection Guide

There are two things you need to know to begin selecting a MAG 2000 sensitivity: shipment weight and fragility (Low, Average, or High). The selection guide (below) should always be used as a starting point only. The MAG 2000 that will be best suited to your application will also take into account product packaging.

Low Fragility Zone

Applicable in situations where both visible and hidden damage is possible and a single extreme impact will cause damage to product.

Average Fragility Zone


Applicable in situations where there is a moderate degree of stability and survivability built into the product and where a standard mode of transportation is used.

High Fragility Zone

Applicable in situations where hidden damage is the key concern. Typically, these products will be constructed of low-tolerance components, such as data storage drives, optical lenses, or any other products that require precise

alignment. The MAG 2000 is available in three different response orientations: HH, VV, and VH.

HH is used to sense horizontal impacts and is mounted to a horizontal surface. VV is used to sense vertical impacts and is mounted to a vertical surface. VH is used to sense horizontal impacts but is mounted to a vertical surface.



Specifications

Sensitivity Range	0.5 - 20G
Impact Duration	0.5 - 50ms
Tolerance	±10% at 20°C / 68°F, 1ATM
Operating Temperature	-20°C to 60°C / -4°F to 140°F
Weight	~31.31g (varies by sensitivity)
Dimensions (LxWxH)	63.5mm x 60.96mm x 20mm
Security	Tamper-resistant, resettable
Adhesive	Acrylic
Adhesive Shelf Life	2 years stored at 20°C / 68°F, 1 ATM
Storage Recommendations	20°C / 68°F, 1 ATM, 0-99% RH non-condensing