



# TiltWatch Tilt Indicators

- Reduces mishandling during transportation or storage
- Provides indisputable evidence of mishandling
- Alerts recipient to inspect contents before acceptance
- Promotes chain of accountability for all product handling
- Confirms effectiveness of packaging
- Helps identify trouble spots in supply chain, from production to transportation and storage
- Helps increase quality of product from dock to dock

When you are shipping networking equipment and electronics, glass and mirrors, or other equipment sensitive to tilt, you need something more than just another 'This End Up' label.

ShockWatch Tilt Indicators detect unacceptable tilting on goods that must remain upright. When these indicators are used, the product cannot be tipped without indisputable evidence of mishandling.

## TiltWatch XTR

The TiltWatch XTR is a single-use tip indicator used to monitor goods that must remain upright. When attached

to a package, the TiltWatch XTR turns red if the package is tilted past 80°. The patented design ensures that the indicator remains unaffected by movement due to normal handling conditions or random vibrations.

## TiltWatch Plus

The TiltWatch Plus indicates whether there has been tilt to the left or right, the degree of the tilt, or if complete overturn has occurred.



TiltWatch XTR Indicator with Companion Label



TiltWatch Plus Indicator with Companion Label



## Selection Guide

	TiltWatch XTR	TiltWatch Plus
<b>Sensor Type</b>	Steel disc, non-metallic	Glass balls
<b>Arming Method</b>	Remove adhesive backing	Remove adhesive backing
<b>Serialised Barcode</b>	Yes	Yes
<b>Indicates Tilt Direction</b>	No	Yes
<b>Indicates Degrees Of Tilt</b>	No	Yes
<b>Inversion Indicator</b>	No	Yes
<b>Activation Angle</b>	Greater than 80°	30° with 10° increments to 90°

## TiltWatch XTR Specifications

<b>Monitoring Range</b>	Single plane
<b>Tolerance</b>	±5° at 20°C / 68°F, 1 ATM
<b>Operating Temperature and Humidity</b>	-40°C to 60°C / -40°F to 140°F 5 – 99% RH, non-condensing
<b>Adhesive</b>	2mm high tack acrylic
<b>Adhesive Shelf Life</b>	2 years
<b>Composition</b>	Rigid polystyrene housing with non-magnetic steel indicator
<b>Dimensions</b>	74.27mm x 60.31mm x 5.29mm
<b>Weight</b>	~14.17g
<b>Installation</b>	Pressure-sensitive adhesive or holes to accommodate screws, nails, or staples
<b>Customisation</b>	Private logos available. Minimum quantity applies

## TiltWatch Plus Specifications

<b>Monitoring Range</b>	Single plane and rollover
<b>Tolerance</b>	±5° at 20°C / 68°F, 1 ATM
<b>Operating Temperature and Humidity</b>	-40°C to 60°C / -40°F to 140°F 5 – 99% RH, non-condensing
<b>Adhesive</b>	Vinyl acetate copolymer
<b>Adhesive Shelf Life</b>	1 year
<b>Composition</b>	Clear PVC housing and glass indicator
<b>Dimensions</b>	116.84mm x 116.84mm x 7.62mm
<b>Weight</b>	~15.30g
<b>Installation</b>	Pressure-sensitive adhesive exposed when liner and arming pin are peeled away